

Standard TFT LCD Modules List

Update: 2025-6-5

NO.		Size	Resolution (R*G*B)	LCD TYPE	DISEA P/N	luminance (cd/m2)	Module Interface	LCD Driver IC	RTP/CTP	CTP Driver IC	Bonding Type	A.A. Dimension(mm) W*H	O.D. Dimension(mm) W*H*D	Oper Temp (°C)
1	0.96"	80x160		IPS	DS-T009HESA-01	200	SPI	ST7735S	NO TP	-	-	10.80x21.70	13.50x27.95x1.87	-20
2	0.99"	128x115	IPS Round	DS-T010BCSA-01	350		SPI/8BIT MCU 24PIN	ST7735S	NO TP	-	-	24.36x21.89	26.71x26.22x1.86	-20
3	1.3"	240x240	IPS Round	DS-T013HQGA-01	500		8BIT MUC/ SPI	GC9A01	NO TP	-	-	32.40x32.40	35.60x38.10x1.57	-10
4	1.3"	240x240	IPS Square	DS-T013BQSA-01	350		SPI/8BIT MCU 24PIN	ST7789	NO TP	-	-	23.40x23.40	26.20x29.22x1.50	-20
5	1.54"	320x320	IPS Square	DS-T015BOSA-01	380		1 LANE MIPI 14PIN	ST7796	NO TP	-	-	27.744x27.744	31.52x33.72x1.45	-20
6	1.77"	128x160	TN	DS-T0177SSI-02	220		8BIT MCU	ILI9163V	NO TP	-	-	28.03x35.04	34.70x46.70x2.60	-20
7	2.0"	240x240	IPS	DS-T020BQSA-01	250		RGB/MCU/SPI 45PIN	ST7789V	NO TP	-	-	30.60x40.80	36.10x51.20x2.35	-20
8	2.0"	320x240	IPS	DS-T020BLIA-01	250		RGB/MCU/SPI 45PIN	ILI9342C	NO TP	-	-	40.80x30.60	46.10x40.96x2.58	-20
9	2.1"	480x480	IPS Round	DS-T021BCSA-02	600		RGB 24bit 40PIN	ST7701S	NO TP	-	-	53.28x53.28	56.18x59.71x2.20	-20
10	2.3"	480x320	IPS	DS-T023BCSA-01	500		2 LANE MIPI 27PIN	ST7701S	NO TP	-	-	46.80x35.10	50.90x45.80x2.45	-20
11	2.4"	240x320	IPS	DS-T024BQSA-01	500		RGB/MCU/SPI 45PIN	ST7789V	NO TP	-	-	36.72x48.96	42.72x59.48x2.20	-20
12	2.7"	240x240	IPS Square	DS-T027BOIA-01	700		RGB 16bit 40PIN	ILI9488	NO TP	-	-	48.96x48.96	53.10x59.00x1.80	-20
13	2.76"	480x480	IPS Round	DS-T0276BCSA-01	280		RGB 24bit 40PIN	ST7701S	NO TP	-	-	70.13x70.13	73.03x76.48x2.26	-20
14	2.8"	240x320	IPS	DS-T028BQSA-01	500		RGB/MCU/SPI 50PIN	ST77789V	NO TP	-	-	43.20x57.60	50.00x69.20x2.35	-20
15	2.8"	240x320	IPS	DS-T028BQSA-01P	400		RGB/MCU/SPI 50PIN	ST77789V	RTP	-	Air bonding	43.20x57.60	50.00x69.20x3.45	-20
16	2.8"	240x320	TN	DS-T028QSW-01	350		RGB/MCU/SPI 50PIN	ST77789V	NO TP	-	-	43.20x57.60	50.00x69.20x2.70	-30
17	2.95"	480x854	IPS	DS-T0295BVSA-01	350		2 LANE MIPI 20PIN	ST7701S	NO TP	-	-	36.72x65.28	43.40x75.27x2.67	-20
18	2.95"	480x854	IPS	DS-T0295BVSA-02	350		SPI+24BIT RGB 45PIN	ST7701S	NO TP			36.72x65.28	43.40x75.27x2.67	-20
19	3.0"	360x640	IPS Bar	DS-T030HUSA-01	350		RGB/MIPI 40PIN	ST7701S	NO TP	-	-	36.72x65.28	43.40x75.27x2.50	-20
20	3.1"	480x800	IPS	DS-T031BVSA-01	400		2 LANE MIPI 27PIN	ST7701S	NO TP	-	-	40.32x67.20	43.68x77.02x1.50	-20
21	3.4"	800x800	IPS Round	DS-T034BOIA-01	1000		4 LANE MIPI 30PIN	ILI9881C	NO TP	-	-	86.60x87.60	99.60x99.79x3.95	-30
22	3.45"	340x800	IPS Bar	DS-T0345BHSA-01	400		RGB 18bit 40PIN	ST7701S	NO TP	-	-	33.97x81.00	37.27x89.00x1.56	-30
23	3.5"	240x320	IPS	DS-T035BQSA-01	300		RGB/MCU/SPI 50PIN	ST7789V	NO TP	-	-	51.27x68.36	54.50x83.00x2.10	-20
24	3.5"	320x480	TN	DS-T035SHL-01	330		RGB 18bit 39PIN	ILI9488	NO TP	-	-	48.96x48.96	54.48x84.71x2.15	-20
25	3.5"	320x480	IPS	DS-T035BHSA-01	320		RGB/MCU/SPI 50PIN	ST7365P	NO TP	-	-	48.96*73.44	54.48x84.71x2.20	-20
26	3.5"	320x480	IPS	DS-T035BHSA-01P	250		RGB/MCU/SPI 50PIN	ST7365P	RTP	-	Air bonding	48.96*73.44	54.48x84.71x3.15	-20
27	3.5"	320x480	IPS	DS-T035QHI-28	650		RGB/MCU/SPI 40PIN	ILI9488	NO TP	-	-	48.96*73.44	55.00x85.20x3.80	-20
28	3.5"	320x480	IPS	DS-T035QHI-03CP	300		RGB/MCU/SPI 50PIN	ILI9488	CTP	GT911	Optical bonding	48.96*73.44	65.61*97.41*3.75	-20
29	3.5"	320x240	TN	DS-T035SLH-01ND	320		RGB 24bit 54PIN	HX8238D	NO TP	-	-	70.08x52.56	76.84x63.84x3.27	-20
30	3.5"	320x240	TN	DS-T035GLH-01	350		RGB 24bit 54PIN	HX8238D	NO TP	-	-	70.08x52.56	76.80x63.90x3.05	-20
31	3.5"	320x240	TN	DS-T035GLH-01P	280		RGB 24bit 54PIN	HX8238D	RTP	-	Air bonding	70.08x52.56	76.80x63.90x4.25	-20
32	3.5"	320x240	TN	DS-T035GLH-01CA	280		RGB 24bit 54PIN	HX8238D	CTP	ST1633i	Air bonding	70.08x52.56	77.00x64.05x5.20	-20
33	3.5"	320x240	TN	DS-T035GLH-02	700		RGB 24bit 54PIN	HX8238D	NO TP	-	-	70.08x52.56	76.80x63.90x3.05	-20
34	3.5"	320x240	TN	DS-T035GLH-02P	650		RGB 24bit 54PIN	HX8238D	RTP	-	Air bonding	70.08x52.56	76.80x63.90x4.25	-20
35	3.5"	320x240	TN	DS-T035GLH-02CA	700		RGB 24bit 54PIN	HX8238D	CTP	ST1633i	Air bonding	70.08x52.56	77.00x64.05x5.20	-20
36	3.5"	320x240	IPS	DS-T035HLS-01	300		RGB888 54PIN	ST7272A	NO TP	-	-	70.08x52.56	76.80x63.90x3.05	-20
37	3.5"	320x240	IPS	DS-T035HLS-01CP	300		RGB 24bit 54PIN	ST7272A	CTP	ST1633i	Optical bonding	70.08x52.56	76.90x64.35x5.10	-20
38	3.5"	320x240	IPS	DS-T035HLS-02	900		RGB 24bit 54PIN	ST7272A	NO TP	-	-	70.08x52.56	76.80x63.90x3.05	-20
39	3.5"	320x240	IPS	DS-T035HLWSA-01	900		RGB 24bit 54PIN	ST7272A	NO TP	-	-	70.08x52.56	76.80x63.90x3.05	-30
40	3.5"	640x480	IPS	DS-T035SGV-01	400		RGB 24bit 54PIN	NV3502C	NO TP	-	-	70.08x52.56	76.74x63.79x3.20	-20
41	3.5"	640x480	IPS	DS-T035SGV-01CP	320		RGB 24bit 54PIN	NV3502C	CTP	ST1633i	Air bonding	70.08x52.56	76.90x64.24x5.09	-20
42	3.5"	800x600	TN	DS-T035TGH-01	250		RGB 24bit 50PIN	HX8282+HX8677	NO TP	-	-	71.28x53.46	64.00x80.00xx4.42	-20
43	3.66"	240x480	IPS Bar	DS-T036BBIA-03	700		MCU/RGB 40PIN	ILI9488	NO TP	-	-	42.00x84.01	48.00x94.91x2.40	-20
44	3.9"	480x128	IPS Bar	DS-T039BPSA-01	1000		RGB 24bit 40PIN	ST7282A	NO TP	-	-	95.04x25.34	105.50x37.00x3.05	-20
45	3.97"	480x800	IPS	DS-T0397BVSA-02	350		SPI+24BIT RGB 45PIN	ST7701S	NO TP	-	-	51.84x86.40	57.14x96.85x2.27	-20

NO.	Size	Resolution (R*G*B)	LCD TYPE	DISEA P/N	luminance (cd/m2)	Module Interface	LCD Driver IC	RTP/CTP	CTP Driver IC	Bonding Type	A.A. Dimension(mm) W*H	O.D. Dimension(mm) W*H*D	Oper Temp(°C)
46	3.97"	480x800	IPS	DS-T0397BVSA-02CP	350	SPI+24BIT RGB 45PIN	ST7701S	CTP	GT911	Optical bonding	51.84x86.40	66.84x111.50x3.75	-20
47	3.99"	400x960	IPS Bar	DS-T0399BUSA-01	450	2 LANE MIPI 30PIN	ST7701S	NO TP	-	-	39.18x94.03	42.90x102.08x2.15	-20
48	4.0"	480x480	IPS Square	DS-T040HCSA-02	400	RGB 18bit 40PIN	ST7701S	NO TP	-	-	71.86x70.18	74.83x78.98x2.18	-20
49	4.0"	720x720	IPS Square	DS-T0395BMSA-01	500	2 LANE MIPI 30PIN	ST7703	NO TP	-	-	71.93x71.93	74.83x78.98x2.08	-20
50	4.0"	720x720	IPS Round	DS-T040BCSA-01	400	4 LANE MIPI 40PIN	SC7707	NO TP	-	-	101.52x106.55	105.61x109.87x2.09	-20
51	4.3"	480x272	TN	DS-T043BPI-01ND	300	RGB 24bit 40PIN	ILI6485	NO TP	-	-	95.04x53.86	105.50x67.15x3.05	-20
52	4.3"	480x272	TN	DS-T043BPS-01ND	250	RGB 24bit 40PIN	ST7282A	NO TP	-	-	95.04x53.86	105.50x67.15x3.05	-20
53	4.3"	480x272	TN	DS-T043BPS-04ND	250	RGB 24bit 40PIN	ST7282A	NO TP	-	-	95.04x53.86	105.50x67.20x2.95	-20
54	4.3"	480x272	TN	DS-T043QPH-58	500	RGB 24bit 40PIN	ILI6480B	NO TP	-	-	95.04x53.86	105.50x67.20x3.00	-20
55	4.3"	480x272	TN	DS-T043QPH-62	600	RGB 24bit 51PIN	ILI6480B	NO TP	-	-	95.04x53.86	105.50x67.20x3.00	-20
56	4.3"	480x272	TN	DS-T043QPS-01	500	RGB 24bit 40PIN	ST7282	NO TP	-	-	95.04x53.86	105.50x67.20x3.00	-20
57	4.3"	480x272	TN	DS-T043QPS-01P	420	RGB 24bit 40PIN	ST7282	RTP	-	Air bonding	95.04x53.86	105.50x67.20x4.10	-20
58	4.3"	480x272	TN	DS-T043QPS-01CA	420	RGB 24bit 40PIN	ST7282	RTP	-	Air bonding	95.04x53.86	105.50x67.20x4.85	-20
59	4.3"	480x272	TN	DS-T043QPS-02	1000	RGB 24bit 40PIN	ST7282	NO TP	-	-	95.04x53.86	105.50x67.20x3.10	-20
60	4.3"	480x272	TN	DS-T043QPS-02P	800	RGB 24bit 40PIN	ST7282	RTP	-	Air bonding	95.04x53.86	105.50x67.20x4.15	-20
61	4.3"	480x272	TN	DS-T043QPS-02CA	800	RGB 24bit 40PIN	ST7282	CTP	ST1633i	Air bonding	95.04x53.86	105.42x67.09x4.85	-20
62	4.3"	480x272	IPS	DS-T043BPSA-01	500	RGB 24bit 40PIN	ST7282A	NO TP	-	-	95.04x53.86	105.50x67.20x2.95	-20
63	4.3"	480x272	IPS	DS-T043BPSA-01P	400	RGB 24bit 40PIN	ST7282A	RTP	-	Air bonding	95.04x53.86	105.50x67.20x4.10	-20
64	4.3"	480x272	IPS	DS-T043BPSA-01CA	400	RGB 24bit 40PIN	ST7282A	CTP	ST1633i	Air bonding	95.04x53.86	105.50x67.20x4.70	-20
65	4.3"	480x272	IPS	DS-T043BPSA-02	1000	RGB 24bit 40PIN	ST7282A	NO TP	-	-	95.04x53.86	105.50x67.20x2.95	-20
66	4.3"	480x272	IPS	DS-T043BPSA-02CP	850	RGB 24bit 40PIN	ST7282A	CTP	ST1633i	Optical bonding	95.04x53.86	105.56x67.26x4.41	-20
67	4.3"	480x800	IPS	DS-T043BVSA-02	400	SPI+24BIT RGB	ST7701S	NO TP	-	-	56.16x93.60	60.86x102.57x2.58	-20
68	4.3"	800x480	IPS	DS-T043BWSA-01	380	RGB 24bit 40PIN	ST7262	NO TP	-	-	95.04x53.86	105.50x67.20x3.00	-20
69	4.3"	800x480	IPS	DS-T043BWSA-02	900	RGB 24bit 40PIN	ST7262	NO TP	-	-	95.04x53.86	105.50x67.20x3.00	-20
70	4.3"	800x480	IPS	DS-T043BWSA-02P	750	RGB 24bit 40PIN	ST7262	NO TP	RTP	Optical bonding	95.04x53.86	105.50x67.20x4.15	-20
71	4.3"	800x480	IPS	DS-T043BWSA-02CP	800	RGB 24bit 40PIN	ST7262	CTP	ST1633i	Optical bonding	95.04x53.86	105.48x67.26x4.41	-20
72	4.3"	800x480	IPS	DS-T043BWSA-27	500	RGB 24bit 40PIN	ST7265	NO TP	-	-	95.04x53.86	105.40x67.10x3.00	-20
73	4.3"	800x480	IPS	DS-T043BWSA-27P	420	RGB 24bit 40PIN	ST7265	NO TP	-	-	95.04x53.86	105.40x67.10x3.00	-20
74	4.3"	800x480	IPS	DS-T043BWSA-28CP	420	RGB 24bit 40PIN	ST7265	CTP	ST1633i	Optical bonding	95.04x53.86	105.40x67.10x4.41	-20
75	4.6"	800x320	TN	DS-T046QWI-01	500	RGB 24bit 40PIN	ILI6137+ILI5960	NO TP	-	-	108.00x43.20	120.7x57.08x2.85	-20
76	5.0"	480x272	TN	DS-T050BPH-01	400	RGB 24bit 40PIN	HX8257A	NO TP	-	-	110.88x62.83	120.70x75.80x3.10	-20
77	5.0"	480x272	TN	DS-T050BPH-01P	300	RGB 24bit 40PIN	HX8257A	RTP	-	Air bonding	110.88x62.83	120.70x75.80x4.30	-20
78	5.0"	480x272	TN	DS-T050BPH-14P	300	RGB 24bit 40PIN	HX8257A	RTP	-	Air bonding	110.88x62.83	120.70x75.80x4.90	-20
79	5.0"	480x272	IPS	DS-T050BPSA-01	400	RGB 24bit 40PIN	ST7282A	NO TP	-	-	110.88x62.83	120.70x75.80x3.00	-20
80	5.0"	640x480	TN	DS-T050QGH-01	300	RGB 24bit 50PIN	TBD.	NO TP	-	-	101.57x76.18	117.65x88.43x5.70	-20
81	5.0"	800x480	TN	DS-T050QWH-04	300	RGB 24bit 40PIN	ILI6122+ILI5960	NO TP	-	-	108.00x64.80	123.26x80.06x2.85	-20
82	5.0"	800x480	TN	DS-T050QWH-01	500	RGB 24bit 40PIN	ILI6122+ILI5960	NO TP	-	-	108.00x64.80	120.70x75.80x3.10	-20
83	5.0"	800x480	TN	DS-T050QWH-01P	400	RGB 24bit 40PIN	ILI6122+ILI5960	RTP	-	Air bonding	108.00x64.80	123.26x80.06x4.30	-20
84	5.0"	800x480	TN	DS-T050QWH-01CA	400	RGB 24bit 40PIN	ILI6122+ILI5960	CTP	ST1633i	Air bonding	108.00x64.80	123.26x80.06x4.80	-20
85	5.0"	800x480	TN	DS-T050QWH-05	1000	RGB 24bit 40PIN	ILI6122+ILI5960	NO TP	-	-	108.00x64.80	123.26x80.06x3.10	-20
86	5.0"	800x480	IPS	DS-T050BWSA-26	550	RGB 24bit 40PIN	ST7265	NO TP	-	-	108.00x64.80	120.70x75.80x2.85	-20
87	5.0"	800x480	IPS	DS-T050BWSA-30CP	500	RGB 24bit 40PIN	ST7265	CTP	ST1633i	Optical bonding	108.00x64.80	123.26x80.06x4.45	-20
88	5.0"	800x480	IPS	DS-T050BWSA-02	1000	RGB 24bit 40PIN	ST7265	NO TP	-	-	108.00x64.80	120.70x75.80x2.85	-20
89	5.0"	800x480	IPS	DS-T050BWSA-02P	850	RGB 24bit 40PIN	ST7265	RTP	-	Air bonding	108.00x64.80	120.70x75.80x4.05	-20
90	5.0"	800x480	IPS	DS-T050BWSA-02CP	700	RGB 24bit 40PIN	ST7265	CTP	ST1633i	Optical bonding	108.00x64.80	123.26x80.06x4.30	-20
91	5.0"	800x480	IPS	DS-T050BWSWA-02	1000	RGB 24bit 40PIN	ST7265	NO TP	-	-	108.00x64.80	120.70x75.80x2.85	-30
92	5.0"	800x480	IPS	DS-T050BWSWA-02CP	850	RGB 24bit 40PIN	ST7265	CTP	ST1633i	Air bonding	108.00x64.80	123.26x80.06x4.60	-30
93	5.65"	640x480	IPS	DS-T0565BGEA-01DE	270	RGB 24bit 50PIN DE Mode	JD9168S	NO TP	-	-	115.20x86.40	126.50x100.00x5.70	-20
94	5.65"	640x480	IPS	DS-T0565BGEA-03DE	350	RGB 18bit 40PIN DE Mode	JD9168S	NO TP	-	-	115.20x86.40	126.50x100.00x5.70	-20
95	5.7"	640x480	IPS	DS-T057BGEA-01DE	500	RGB 18bit 40PIN DE Mode	JD9168S	NO TP	-	-	115.20x86.40	127.00x98.43x5.80	-20
96	5.7"	640x480	IPS	DS-T057BGEA-01PDE	420	RGB 18bit 40PIN DE Mode	JD9168S	RTP	-	Air bonding	115.20x86.40	127.00x98.43x7.60	-20
97	6.8"	480x1280	IPS Bar	DS-T068BZSA-01	450	4 LANE MIPI 40PIN	FL7707N	NO TP	-	-	160.51x60.19	181.20x66.85x4.70	-20

No.	Size	Resolution (R*G*B)	LCD TYPE	DISEA P/N	Luminance (cd/m2)	Module Interface	LCD Driver IC	RTP/CTP	CTP Driver IC	Bonding Type	A.A.		O.D.		Open Temp (°C)
											Dimension(mm) W*H	Dimension(mm) W*H*D			
98	7.0"	280x1424	IPS Bar	DS-T070BUSA-01	350	4 LANE MIPI 40PIN	ST7703i	NO TP	-	-	33.60x170.88	38.20x181.47x3.45	-20		
99	7.0"	800x480	TN	DS-T070SWH-83	350	RGB 24bit 50PIN	HX8264E+HX8664B	NO TP	-	-	154.08x85.92	164.90x100.00x3.45	-20		
100	7.0"	800x480	TN	DS-T070BWE-14ND	300	RGB 24bit 50PIN Short FPC	EK9716DB4+EK7300AB2	NO TP	-	-	153.84x85.63	164.90x100.00x5.60	-20		
101	7.0"	800x480	TN	DS-T070QWE-01ND	300	RGB 24bit 50PIN Short FPC	EK9713CA+EK73002ABA	NO TP	-	-	154.08x85.92	164.90x100.00x5.60	-20		
102	7.0"	800x480	TN	DS-T070QWE-01PD	250	RGB 24bit 50PIN Short FPC	EK9713CA+EK73002ABA	RTP	-	Air bonding	154.08x85.92	164.90x100.00x7.20	-20		
103	7.0"	800x480	TN	DS-T070QWE-01AD	250	RGB 24bit 50PIN Short FPC	EK9713CA+EK73002ABA	CTP	ST1633i	Air bonding	154.08x85.92	184.81x116.52x7.79	-20		
104	7.0"	800x480	TN	DS-T070QWE-03ND	300	RGB 24bit 50PIN Short FPC	EK9713CA+EK73002ACGB	NO TP	-	-	154.08x85.92	164.90x100.00x3.40	-20		
105	7.0"	800x480	TN	DS-T070SWH-19	800	RGB 24bit 50PIN Short FPC	HX8264E+HX8664B	NO TP	-	-	154.08x85.92	165.00x100.00x5.70	-20		
106	7.0"	800x480	TN	DS-T070QWE-02ND	300	RGB 24bit 50PIN Long FPC	EK9713CA+EK73002ABA	NO TP	-	-	154.08x85.92	164.90x100.00x5.60	-20		
107	7.0"	800x480	TN	DS-T070BWE-44ND	300	RGB 24bit 50PIN Long FPC	EK9716DB4+EK7300AB2	NO TP	-	-	153.84x85.63	164.90x100.00x5.60	-20		
108	7.0"	800x480	TN	DS-T070QWHW-01	550	RGB 24bit 50PIN Long FPC	HX8264E+HX8664B	NO TP	-	-	154.08x85.92	164.95x100.00x5.70	-30		
109	7.0"	800x480	TN	DS-T070QWHW-01P	480	RGB 24bit 50PIN Long FPC	HX8264E+HX8664B	RTP	-	Air bonding	154.08x85.92	165.00x100.00x6.85	-30		
110	7.0"	800x480	TN	DS-T070QWHW-01CA	500	RGB 24bit 50PIN Long FPC	HX8264E+HX8664B	CTP	ST1633i	Air bonding	154.08x85.92	184.81x116.52x8.00	-30		
111	7.0"	800x480	TN	DS-T070QWHW-02	1000	RGB 24bit 50PIN Long FPC	HX8264E+HX8664B	CTP	-	-	154.08x85.92	184.81x116.52x8.00	-30		
112	7.0"	800x480	TN	DS-T070QWHW-02P	850	RGB 24bit 50PIN Long FPC	HX8264E+HX8664B	RTP	-	Air bonding	154.08x85.92	165.00x100.00x7.30	-30		
113	7.0"	800x480	TN	DS-T070QWHW-02CA	850	RGB 24bit 50PIN Long FPC	HX8264E+HX8664B	CTP	ST1633i	Air bonding	154.08x85.92	184.81x116.52x8.00	-30		
114	7.0"	800x480	TN	DS-T070QWHW-03CA	400	RGB 24bit 50PIN Long FPC	HX8264E+HX8664B	CTP	ILI2511	Air bonding	154.08x85.92	164.95x100.00x7.60	-30		
115	7.0"	800x480	IPS	DS-T070KWSA-01	500	RGB 24bit 50PIN Short FPC	ST7277	NO TP	-	-	153.84x85.63	165.00x100.00x5.70	-20		
116	7.0"	800x480	IPS	DS-T070KWSA-01CA	430	RGB 24bit 50PIN Short FPC	ST7277	CTP	ST1633i	Air bonding	153.84x85.63	184.81x116.52x8.00	-20		
117	7.0"	800x480	IPS	DS-T070KWSA-01CP	450	RGB 24bit 50PIN Short FPC	ST7277	CTP	ST1633i	Optical bonding	153.84x85.63	184.81x116.52x7.65	-20		
118	7.0"	800x480	IPS	DS-T070MWRA-01	400	RGB 18bit 40PIN	RM53052+RM57452	NO TP	-	-	152.40x91.44	165.00x104.60x5.30	-20		
119	7.0"	800x480	IPS	DS-T070SWHA-01	1000	LVDS 6/8bit 20PIN	HX8249-A01+HX8678-C01	NO TP	-	-	152.40x91.44	169.80x109.70x8.90	-30		
120	7.0"	800x480	IPS	DS-T070SWHA-02	500	LVDS 6/8bit 20PIN	HX8249-A01+HX8678-C01	NO TP	-	-	152.40x91.44	169.80x109.70x8.90	-30		
121	7.0"	1024x600	TN	DS-T070QAE-01ND	300		EK79001HI+EK73215BCGA	NO TP	-	-	154.21x85.92	164.90x100.00x3.40	-20		
122	7.0"	1024x600	TN	DS-T070BAHA-01	500		HX8282A11+HX8696A01	NO TP	-	-	154.21x85.92	164.80x99.80x5.65	-20		
123	7.0"	1024x600	TN	DS-T070BAHA-01CA	400		HX8282A11+HX8696A01	CTP	ST1633i	Air bonding	154.21x85.92	184.81x116.52x8.00	-20		
124	7.0"	1024x600	TN	DS-T070BAHA-01CP	420		HX8282A11+HX8696A01	CTP	ST1633i	Optical bonding	154.21x85.92	184.81x116.52x7.55	-20		
125	7.0"	1024x600	TN	DS-T070BAHA-01-B2	500	LVDS 20PIN	HX8282A11+HX8696A01	NO TP	-	-	154.21x85.92	165.00x100.00x5.70	-20		
126	7.0"	1024x600	TN	DS-T070BAHA-03	500	RGB 24bit 50PIN	HX8282A11+HX8696A01	NO TP	-	-	154.21x85.92	164.80x99.80x5.70	-20		
127	7.0"	1024x600	TN	DS-T070BAHA-03P	400	RGB 24bit 50PIN	HX8282A11+HX8696A01	RTP	-	Air bonding	154.21x85.92	164.90x100.00x7.20	-20		
128	7.0"	1024x600	TN	DS-T070BAHA-03CA	400	RGB 24bit 50PIN	HX8282A11+HX8696A01	CTP	ILI2511	Air bonding	154.21x85.92	165.40x100.03x7.60	-20		
129	7.0"	1024x600	TN	DS-T070BAHA-03CP	420	RGB 24bit 50PIN	HX8282A11+HX8696A01	CTP	ILI2511	Optical bonding	154.21x85.92	165.35x100.03x7.05	-20		
130	7.0"	1024x600	TN	DS-T070BAEA-27ND	550	RGB 24bit 50PIN	JD9165BA	NO TP	-	-	154.21x85.92	164.90x100.00x5.60	-20		
131	7.0"	1080x1080	IPS Round	DS-T070TOSA-01	350	4 LANE MIPI 30PIN	FL5893DC	NO TP	-	-	177.55x177.55	186.25x191.38x5.06	-20		
132	7.8"	400x1280	IPS	DS-T078VYRA-01	600	4 LANE MIPI 40PIN	OTA7290N	NO TP	-	-	59.40x190.08	67.60x205.78x7.25	-20		
133	8.0"	800x600	TN	DS-T080QGH-03	500	RGB 24bit 50PIN	TBD.	NO TP	-	-	162.00x121.50	183.00x141.00x6.20	-20		
134	8.0"	800x600	TN	DS-T080QGH-07P	400	RGB 24bit 50PIN	TBD.	RTP	-	Air bonding	162.00x121.50	183.00x141.00x8.10	-20		
135	8.0"	800x600	TN	DS-T080QGH-09	1200	RGB 24bit 50PIN	TBD.	NO TP	-	-	162.00x121.50	183.00x141.00x5.20	-20		
136	8.0"	800x1280	IPS	DS-T080BYGA-01	300	4 LANE MIPI 40PIN	GH8555BL	NO TP	-	-	107.64x172.22	114.66x184.16x2.80	-20		
137	8.0"	800x1280	IPS	DS-T080BYEA-01ND	300	4 LANE MIPI 31PIN	JD9365DA-H3	NO TP	-	-	107.64x172.22	114.66x184.16x2.60	-20		
138	8.0"	1024x768	IPS	DS-T080BXEWA-01	300	LVDS 6/8bit 40PIN	JD9165A	NO TP	-	-	162.05x121.54	174.00x136.00x2.60	-30		
139	8.0"	1024x768	IPS	DS-T080BXEA-01CP	250	LVDS 6/8bit 40PIN	JD9165A	CTP	ST1633i	Optical bonding	162.05x121.54	180.30x142.30x4.63	-30		
140	10.1"	800x1280	IPS	DS-T101BYEA-01ND	300	4 LANE MIPI 31PIN	JD9365DA-H3	NO TP	-	-	135.36x216.58	143.00x228.67x2.50	-30		
141	10.1"	1024x600	TN	DS-T101BAE-01ND	530	RGB 24bit 50PIN	EK79001HJ3/EK73215BCGA	NO TP	-	-	222.72x125.28	235.00x143.00x5.00	-20		
142	10.1"	1024x600	TN	DS-T101BAE-01PD	450	RGB 24bit 50PIN	EK79001HJ3/EK73215BCGA	RTP	-	Air bonding	222.72x125.28	235.00x143.00x6.6	-20		
143	10.1"	1024x600	TN	DS-T101BAH-01	380	LVDS 6/8bit 40PIN	HX8282A11+HX8696A01	NO TP	-	-	222.72x125.28	235.00x143.00x5.10	-20		
144	10.1"	1024x600	IPS	DS-T101BAHA-01	500	LVDS 6/8bit 40PIN	HX8282A11+HX8696A01	NO TP	-	-	222.72x125.28	235.00x143.00x5.20	-20		
145	10.1"	1024x600	IPS	DS-T101BAHA-02CP	420	LVDS 6/8bit 40PIN	HX8282A11+HX8696A01	CTP	ILI2511	Optical bonding	222.72x125.28	235.10x143.10x6.98	-20		
146	10.1"	1024x600	IPS	DS-T101BAHA-02ND	400	RGB 24bit 50PIN	HX8282A11+HX8696A01	NO TP	-	-	222.72x125.28	235.00x143.00x5.00	-20		
147	10.1"	1280x800	IPS	DS-T101BIHA-01	330	8BIT LVDS 40PIN	TBD.	NO TP	-	-	216.96x135.60	229.56x149.16x2.67	-20		
148	10.1"	1280x800	IPS	DS-T101HIEWA-01	1000	LVDS 6/8bit 40PIN	EK79202	NO TP	-	-	216.96x135.60	229.46x149.10x4.80	-30		
149	10.1"	1280x800	IPS	DS-T101HIEWA-01CP	850	LVDS 6/8bit 40PIN	EK79202	CTP	ILI2511	Optical bonding	216.96x135.60	260.00x170.00x6.95	-30		

NO.	Size	Resolution (R*G*B)	LCD TYPE	DISEA P/N	luminance (cd/m2)	Module Interface	LCD Driver IC	RTP/CTP	CTP Driver IC	Bonding Type	A.A.	O.D.	Oper Temp (°C)
											Dimension(mm) W*H	Dimension(mm) W*H*D	
150	10.1"	1280x800	IPS	DS-T101HIEWA-03	1000	LVDS 6/8bit 40PIN	EK79202	NO TP	-	-	216.96x135.60	229.46x149.10x4.80	-30
151	10.1"	1280x800	IPS	DS-T101HIEWA-04	500	LVDS 6/8bit 40PIN	EK79202	NO TP	-	-	216.96x135.60	229.46x149.10x4.80	-30
152	10.1"	1280x800	IPS	DS-T101QIHA-01CA-B	300	HDMI 19PIN	TBD.	CTP	ILI2511	Air bonding	216.96x135.60	240.00x163.50x13.00	-20
153	10.1"	1920x1200	IPS	DS-T101BFHA-01	1200	LVDS 2CHANNEL 8BIT 45PIN	TBD.	NO TP	-	-	216.81x135.50	228.72x148.36x4.51	-20
154	10.4"	800x600	TN	DS-T104QGH-01	350	LVDS 8bit 20PIN	TBD.	NO TP	-	-	211.20x158.40	236.00x176.90x5.60	-20
155	10.4"	800x600	TN	DS-T104QGH-02	400	RGB 24bit 60PIN	TBD.	NO TP	-	-	211.20x158.40	228.50x175.50x5.0	-10
156	10.4"	1024x768	IPS	DS-T104QXHA-03	1000	LVDS 6/8bit 30PIN	TBD.	NO TP	-	-	210.43x127.70	238.60x175.80x6.45	-20
157	11.6"	1920x1080	IPS	DS-T116BFHA-01	500	eDP 30PIN	TBD.	NO TP	-	-	256.32x144.18	267.72x164.42x6.10	0~
158	12.1"	800x600	TN	DS-T121QGH-01	400	LVDS 6/8bit 20PIN	TBD.	NO TP	-	-	246.00x184.50	279.00x209.00x9.00	-20
159	12.1"	1024x768	IPS	DS-T121QXHA-01	1000		TBD.	NO TP	-	-	245.76x184.32	260.50x204.00x7.11	-20
160	12.1"	1024x768	IPS	DS-T121QXHA-02	600	LVDS 6/8bit 30PIN	TBD.	NO TP	-	-	210.43x127.70	260.50x204.00x7.20	-30
161	12.1"	1280x800	IPS	DS-T121QIHA-01	550		TBD.	NO TP	-	-	261.12x163.20	278.00x184.00x10.00	-20
162	12.1"	1280x800	IPS	DS-T121BIHA-01	1000	LVDS 8bit 40PIN	TBD.	NO TP	-	-	261.12x163.20	277.70x180.60x6.00	-20
163	13.3"	1920x1080	IPS	DS-T133BFHA-02	400		TBD.	NO TP	-	-	293.76x165.24	307.80x183.25x5.20	-20
164	15.0"	1024x768	IPS	DS-T150QXHA-01	450	LVDS 8bit 20PIN	TBD.	NO TP	-	-	304.13x228.10	326.50x253.50x9.58	-20
165	15.6"	1920x1080	IPS	DS-T156QFHWA-01	1000	LVDS 2CHANNEL 8BIT 40PIN	TBD.	NO TP	-	-	344.16x193.59	363.80x215.90x9.30	-30
166	15.6"	1920x1080	IPS	DS-T156BFHWA-02	1000		TBD.	NO TP	-	-	344.16x193.59	360.10x212.55x6.05	-30
167	15.6"	1920x1080	IPS	DS-T156BFHWA-02CP	850		TBD.	CTP	ILI2511	-	344.16x193.59	360.10x212.55x9.05	-30
168	18.5"	1920x1080	IPS	DS-T185BFHWA-02	1500	LVDS 2CHANNEL 30PIN	TBD.	NO TP	-	-	408.96x230.04	430.37x254.60x11.2	-30
169	21.5"	1920x1080	IPS	DS-T215BFHA-02	1000		TBD.	NO TP	-	-	476.64x268.11	495.60x292.20x10.57	-20