


Category: 固定式端子/Plug-in terminal-plug

Product name: 2454XX

Product Description: 10.0mm , 1000V , 32A CE



Product Picture



基本信息 /Basic Information

产品型号 SUPU ID	2454XX
产品间距 Pitch	10.0mm
产品层数 Number of levels	1
产品位数 Number of connections	2P-24P
接线方式 Connection method	回拉式弹簧接线Spring cage connection
防护等级 Protection Level	IP20

工作温度 Work temperature	-40~+105℃
--------------------------	-----------

IEC数据 /IEC Data

额定电流 Rated Current	32A		
额定电压 Rated Voltage	1000V		
过压类别 Overvoltage category	III	III	II
污染等级 Pollution degree	3	2	2
额定冲击电压 Rated impulse voltage	8.0KV	8.0KV	8.0KV
额定电压 Rated Voltage	630V	1000V	1000V
硬导线截面积 Conductor cross section solid	0.2-4.0mm ²		
柔性导线截面积 Conductor cross section flexible	0.2-4.0mm ²		
柔性导线截面积，带绝缘管套 Conductor cross section flexible,with furrule	0.2-4.0mm ²		
锁线螺钉规格 Locking screw Specification	-		
额定扭矩 Rated Torque	-		
固定螺钉规格 Fixed Screw Specification	-		
额定扭矩 Rated Torque	-		
剥线长度 Stripping length	8-9mm		

UL数据 /UL Data

使用组别 Use group	B	C	D
额定电流 Rated Current	20A	20A	10A
额定电压 Rated Voltage	300V	150V	300V

额定接线容量	24-12AWG
Rated cross section	

材料信息 /Material Data

绝缘材料	PA66
Insulation material	
绝缘材料组别	I
Insulation material group	
阻燃等级，符合UL94	V0
Flame retardant grade, UL94 compliance	
导电体材料	Copper alloy
Contact material	
导电体表面镀层	Sn,Plated
Surface characteristics	

产品认证 /Product Certification

认证图标	
Certificate	

UL证书号	
UL file No.	

VDE证书号	
VDE No.	

TUV证书号	
TUV No.	

Ningbo Supu Electronics Co.,Ltd	Address: No. 625, Kandun Town Street, Cixi
	City, Zhejiang Province
Zip code: 315303	Switchboard: +86 574-63288158
Fax: +86 574-63288170	E-mail : askme@supu.cn
E-mail : askme@supu.cn	Service Hotline: 400-626-6336



Code