


Category: 插拔式端子-插座/Plug-in terminal-plug

Product name: MC-PAL5.0H04-0002

Product Description: 5.0mm , 320V , 12A CE

Product Picture



基本信息 /Basic Information

产品型号
SUPU ID MC-PAL5.0H04-0002

产品间距
Pitch 5.0mm

产品层数
Number of levels 1

产品位数
Number of connections 4P

接线方式
Connection method -

防护等级
Protection Level IP20

工作温度	-40~+105℃		
Work temperature			

IEC数据 /IEC Data

额定电流	12A		
Rated Current			
额定电压	320V		
Rated Voltage			
过压类别	III	III	II
Overvoltage category			
污染等级	3	2	2
Pollution degree			
额定冲击电压	4KV	4KV	4KV
Rated impulse voltage			
额定电压	250V	320V	400V
Rated Voltage			
硬导线截面积	-		
Conductor cross section solid			
柔性导线截面积	-		
Conductor cross section flexible			
柔性导线截面积，带绝缘管套	-		
Conductor cross section flexible,with furrule			
锁线螺钉规格	-		
Locking screw Specification			
额定扭矩	-		
Rated Torque			
固定螺钉规格	-		
Fixed Screw Specification			
额定扭矩	-		
Rated Torque			
剥线长度	-		
Stripping length			

UL数据 /UL Data

使用组别	B	C	D
Use group			
额定电流	16A	-	10A
Rated Current			
额定电压	300V	-	300V
Rated Voltage			

额定接线容量	
Rated cross section	-

材料信息 /Material Data

绝缘材料	PA66
Insulation material	
绝缘材料组别	I
Insulation material group	
阻燃等级，符合UL94	V0
Flame retardant grade, UL94 compliance	
导电体材料	Copper alloy
Contact material	
导电体表面镀层	Sn,Plated
Surface characteristics	

产品认证 /Product Certification

认证图标	
Certificate	
UL证书号	
UL file No.	
VDE证书号	
VDE No.	
TUV证书号	
TUV No.	

Ningbo Supu Electronics Co.,Ltd

Zip code: 315303

Fax: +86 574-63288170

E-mail : askme@supu.cn

Address: No. 625, Kandun Town Street, Cixi

City, Zhejiang Province

Switchboard: +86 574-63288158

E-mail : askme@supu.cn

Service Hotline: 400-626-6336



Code